



**5 ANS
GARANTIE**



SPECIFICATIONS

REFERENCES	PUISSANCE	QUANTITE DE LED	LED MARQUE	LUMENS	CERTIFICATIONS
PLAFON-TUN-3030-40W	40W	1	PHILIPS 3030 2D	5200	CE /ROHS
PLAFON-TUN-3030-50W	50W			6250	CE /ROHS
PLAFON-TUN-3030-80W	80W	2		10400	CE /ROHS
PLAFON-TUN-3030-100W	100W			12500	CE /ROHS
PLAFON-TUN-3030-120W	120W	3		15600	CE /ROHS
PLAFON-TUN-3030-150W	150W			18750	CE /ROHS
PLAFON-TUN-3030-160W	160W	4		20800	CE /ROHS
PLAFON-TUN-3030-200W	200W			25000	CE /ROHS


INFORMATIONS COMPLEMENTAIRES

Voltage	100-240 /277Vac /50 /60Hz
CRI	>70
Protection	IP66, IK10
Efficacité lumineuse	125~130lm /w
Materiaux	Alliage d'Aluminium
Installation	Ajustable selon l'installation
Maintenance	L70>100,000 hours

INFORMATIONS POUR DEVIS


Designation	Lanterne-Led-Model_Lampe-puissance
Marque	EnergieDouce
LED Marque	PHILIPS LUXEON 3030 2D
Angle	60°, 90°, 110°
Chaleur	4000 /5000 /5700K
Coloris	Argent
En option	-

DIMENSIONS




Nombre de Modules	1	2	3	4
"L" Long.	166 mm	239 mm	312 mm	385 mm
Poids	2.3 kg	3.5 kg	4.4 kg	5.2 kg

EMBALLAGE




Nombre de Modules	1	2	3	4
"L" Long.	285 mm	355 mm	430 mm	505 mm
Poids	3.0 kg	4.3 kg	5.2 kg	6.1 kg


FLUX LUMINEUX




Lens code: Typel,Medium



Lens code: Typell,Medium



Lens code: Typelll,Medium



Lens code: TypeV,Short